



## iM2050 Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2050**  
Standard



**iM2050-X0000**  
No Foam



**iM2050-X0002**  
With Padded Dividers



**iM2050-X0001**  
With Foam

### DIMENSIONS

|                              |                                             |
|------------------------------|---------------------------------------------|
| <b>Interior (L×W×D)</b>      | 9.50 x 7.50" x 4.25 (24.1 x 19.1 x 10.8 cm) |
| <b>Exterior (L×W×D)</b>      | 11.80 x 9.80" x 4.70 (30 x 24.9 x 11.9 cm)  |
| <b>Lid Depth</b>             | 1.50" (3.8 cm)                              |
| <b>Bottom Depth</b>          | 2.75" (7 cm)                                |
| <b>Total Depth</b>           | 4.25" (10.8 cm)                             |
| <b>Int Volume</b>            | 0.18 ft³ (0.005 m³)                         |
| <b>Padlock Hole Diameter</b> | 0.28" (0.7 cm)                              |

### MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM                                         |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |

**Purge Vent**

Gortex membrane

## COLOURS

 Black OD Green Yellow

## WEIGHT

|                           |                     |
|---------------------------|---------------------|
| <b>Weight With Foam</b>   | 3.00 lbs (1.4 kg)   |
| <b>Weight Empty</b>       | 2.70 lbs (1.2 kg)   |
| <b>Buoyancy</b>           | 11.10 lbs (5 kg)    |
| <b>Master Pack Weight</b> | 23.20 lbs (10.5 kg) |

## TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

## CERTIFICATIONS

**IP67**

## OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 6   |
| <b>Military</b>    | yes |

## ACCESSORIES



**iM2050-FOAM**  
3 pc. Replacement Foam Set



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**iM20XX-M4-BEZEL**  
Base Bezel Kit (Metric)

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 06-01-24